

L5 DIGITAL

Accurate, affordable, self-leveling rotary laser



- **Compensator self-leveling**
Keeps you on the level all day
- **3/16" @100' accuracy** (4.8mm @30m)
Helps you do your best work
- **360° rotating beam**
No need to re-aim for every shot
- **Vertical plane capability**
Maximum alignment options
- **90° / plumb beam**
Do layouts or transfer points
- **1000' dia.** (304m) **with receiver**
Cover the big sites in one setup

PRO SHOT™

NEW!

**NI-MH RECHARGEABLE BATTERY
KIT NOW AVAILABLE. GOOD FOR 45
OPERATING HOURS BETWEEN CHARGES.**



Take Your Best Shot

The Pro Shot™ **L5** laser system gives you what you need to do the job right. Self-leveling, a bright red rotating beam, vertical plane/90° capability, a plumb spot and beam scanning.

Use it indoors, use it outdoors, use it with confidence because the **L5's** self-leveling won't let you take a bad elevation shot.

Every Pro Shot™ laser will perform as advertised, *or better!* Some laser brands try to sell you with a decent accuracy spec., but don't even come close to making it. Don't bet the outcome of your jobs on a laser that can't deliver the performance you need.

After more than 12 years making our Pro Shot™ brand and 28 years in the laser business, we know what it takes to build a professional grade laser. That's why we make the **L5**.

- Top quality, high performance, built to last.
- The one laser tool for all your alignment needs.
- Designed for professional builders.

VM2 Vertical Mount

The optional **VM2** mount lets you setup to project a vertical plane for alignment, or use

the 90° plumb beam and the vertical plane as a square reference for layout work. Mount it to a tripod, or attach it to a wall for use as a basic ceiling or soffit mount.



W1 Bracket

The optional **W1** bracket is used for installing suspended ceilings. The **W1** clamps to the wall angle for fast setups and the laser height is adjustable.



L5 Laser Specifications

Range with R6 receiver	500' rad. / 1000' dia. (152m/304m)
Leveling accuracy	±30 arc sec. (±3/16" per 100') (±4.8mm per 30m)
Self leveling range	±10 arc minutes
Compensator type	Wire hung, air damped
Vertical capability	Built-in vial, optional mount
Rotational coverage	360 degrees
Scan angle selections	15°, 30°, 45°, 90° (nominal)
Rotation speed	Variable in steps: 0 to 450 rpm
Rotating beam power	2.0mW (nominal)
Auto shut-off (level mode)	When off-level > 30 minutes
Power supply	Two D-cell batteries
Battery life	70 hours (alkaline)
Rechargeable batteries	Optional Ni-Mh kit available
Environmental	Dust and water resistant
Warranty	12 Months defects coverage
Safety	CDRH Class IIIa, IEC Class 3R
Operating temperature	14°F to 122°F (-10°C to 50°C)
Storage temperature	-40°F to 140°F (-40°C to 60°C)

R5e Receiver

The optional **R5e** lets you take elevation and alignment readings when conditions make it difficult to see the beam. Required when working in direct sunlight, where laser beams can't safely or legally be bright enough to be seen and for long distance work. An LCD display and audio tone indicate when the **R5e** is high, low, or on.



www.proshotlaser.com



151 Martinvale Lane • San Jose, CA 95119 USA • Tel: 1.800.238.0685 • Fax: 1.408.361.3180

Contact Your Pro Shot™ Dealer Today:

